



OSIGHT SE

Large and In Charge, 6 MOA

	6 MOA Red Dot		Enclosed Emitter Optic
	Side-Loading CR1620 Battery		Aspherical Lens
	RMsC Footprint		Motion Sensor



OSIGHT SE

Large and In Charge, 6 MOA

Market Applications

Everyday Carry, Concealed Carry, Self-Defense, Home Protection

UPC

6978095650438

DESCRIPTION

The Osight SE 6 MOA is a precision-engineered enclosed emitter optic built for reliable performance in demanding conditions. A 6 MOA red dot enables fast target acquisition and forgiving alignment, making it ideal for high-stress scenarios such as self-defense, home defense, and tactical use. The larger dot is easy to pick up under recoil and rapid movement, supporting quicker follow-up shots, while its familiar visual profile ensures consistent performance across diverse lighting conditions — delivering confident aim and immediate engagement. The fully enclosed system with a distortion-free aspherical lens protects against dust, moisture, and debris while maintaining clear, consistent sight pictures. A side-loading CR1620 battery enables quick replacement without removing the optic, while motion-activated wake and low power indication ensure it is always ready when needed. With a low-deck height for direct co-witness with most factory iron sights and an RMSc footprint for broad compatibility, the SE 6 MOA integrates seamlessly across handgun platforms. Ten brightness settings, including two night vision levels, along with a memory function for last-used settings, complete a compact CNC-machined 7075-T6 aluminum design built for dependable everyday carry and tactical performance.



FEATURES

- **6 MOA Red Dot:** A 6 MOA red dot enables faster target acquisition and more forgiving alignment, making it highly effective in high-stress scenarios such as self-defense, home defense, and tactical use. The larger dot is easier to pick up under recoil and rapid movement, supporting quicker follow-up shots. With its familiar and consistent visual profile, the red reticle performs reliably across diverse lighting conditions, delivering confident aim and immediate engagement.
- **Enclosed Emitter Optic:** With a fully enclosed system, the optic offers unmatched protection against the elements, ensuring reliable performance in any environment.
- **Side-Loading CR1620 Battery:** Effortless battery replacement without removing the optic ensures hassle-free re-zeroing. A high-end CR1620 battery offers easy accessibility while maintaining steady performance.
- **Aspherical Lens:** The aspherical lens ensures zero distortion, parallax-free performance, and exceptional clarity for rapid, precise target acquisition.
- **RMSc Footprint:** Fitting directly to your optics-ready slides, the compact optic delivers exceptional compatibility, ensuring seamless integration across a multitude of builds.
- **Motion Sensor Function:** The Osight SE 6 MOA powers on at the slightest movement, and powers down after 3 minutes of inactivity to conserve battery.
- **Low Power Indication:** If battery voltage drops below 2.2V, the reticle will quickly triple-flash once per minute to recommend a battery replacement.
- **Sleek Battery Tray:** With a sleek and streamlined battery tray design, the Osight SE 6 MOA stays comfortable to carry, quick to draw, and ideal for concealed or tactical use.
- **Low-Deck Height:** The low-deck height provides a perfect co-witness with most factory iron sights, eliminating the need for lower 1/3 or suppressor-height sights.
- **10 Brightness Settings:** 8 daylight and 2 night vision settings — compatible levels for versatility in any demands.
- **CNC-Machined Aircraft-Grade 7075-T6 Aluminum:** The optic is nearly indestructible with CNC-machined aircraft-grade 7075-T6 aluminum housing, ensuring durability and a professional edge over time.
- **Memory Function:** Once activated, the built-in memory function returns to the last selected brightness level, allowing users to focus on the target without distraction.

RUNTIME & BRIGHTNESS

Reticle		
Mode 3	63,000 H	

Settings	Night Vision	Day Light
Brightness	(Lowest) Level 1-2	Level 3-10 (Brightest)

OSIGHT SE

Large and In Charge, 6 MOA

SPECIFICATIONS

Optic	Osight SE 6 MOA
Reticle Type	6 MOA Dot
Reticle Color	Red
Emitter	Enclosed
Light Wavelength	650 nm
Adjustment Per Click	1 MOA
W&E Travel Range	± 35 MOA
Battery Life	63,000 H (Mode 3)
Power Source	CR1620
Brightness Settings	8 DL & 2 NV
Window Size	0.83 x 0.55 in 21 x 14 mm
Magnification	1×
Aspherical Lens	Yes
Parallax Free	Yes
Unlimited Eye Relief	Yes
Motion Sensor Function	Yes
Memory Function	Yes
Multi-Coatings	Yes
Housing Material	CNC-Machined Aircraft-Grade 7075-T6 Aluminum
Waterproof Rating	IPX7
Dimensions	1.59 x 0.98 x 0.97 in 40.4 x 25 x 24.7 mm
Weight	0.97 oz / 27.5 g

⚠ WARNING


- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours**.
- **KEEP** new and used batteries **OUT OF REACH** of **CHILDREN**.
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.



WATERPROOF
IPX7



COMPLIANCE
CAN ICES-003 (B) / NMB-003 (B)



WARRANTY



www.osight.com/lifetime-warranty

OPTIONAL ACCESSORY

RMR-to-RMSc Adapter Plate

IN THE BOX

Optic (CR1620 battery included)	Screw Box
Adjustment Tool	Osight Sticker
READ ME card	Cleaning Cloth
3 × M3*10.5 mm Screws	Safety Warnings
3 × M3*11.5 mm Screws	User Manual
3 × M4*9.4 mm Screws	
3 × M4*10.5 mm Screws	
3 × #6-32*0.433 in Screws	
3 × #6-40*0.374 in Screws	
3 × #6-40*0.449 in Screws	
2 × Spare Battery Compartment Screws	



Note: The Osight SE 6 MOA **MUST** be mounted properly by applying non-permanent (medium/blue) threadlocker to the included screws. AND torque each screw to 15-17 in-lbs (suggested torque value in the READ ME card). If an adapter plate is required, please follow the manufacturer's installation instructions.



www.osight.com