ORH-193 Picatinny Riser Mount

I. Application

Mounting the Osight R on firearms equipped with a Picatinny rail







II. Description

The ORH-193 securely mounts the Osight R to a Picatinny rail and positions the optic centerline at 1.93 inches. Its compact, Type III hard-anodized 6061 aluminum body, steel clamp, and robust rail-locking screw provide a durable and secure mounting platform.

III. Specifications

- **Dimension:** 2.48 × 1.42 × 1.18 in / 63 × 36 × 30 mm
- **Weight:** 2.15 oz / 61 g
- **Material:** Aircraft-Grade 6061 Aluminum
- **Color:** Matte Black
- **Impact:** 1,000G
- **Warranty:** 2 years
- **Optical Center Height:** 1.93 in / 49.0 mm, above the rail with the Osight R installed

IV. Installation Torque

- M3 / Torque: ≤12 in-lb
- M5 / Torque: ≤43 in-lb

V. In The Box

- ORH-193 Picatinny Riser Mount
- T10 L-Shaped Torx Wrench

- T25 L-Shaped Torx Wrench
- 4 × M3 Screws



VI. Warning

- Keep the mount and small parts out of reach of children.
- Do not disassemble the mount or expose it to temperatures above 70°C (158°F), saltwater, or corrosive liquids.

VII. Notice

- Secure the Osight R to the mount using the four supplied M3 screws. Do not exceed 12 in-lb of torque.
- Secure the mount to the Picatinny rail using the M5 screw. Do not exceed 43 in-lb of torque.
- Wear and tear from saltwater use will void the warranty.